Index to

EXPERIMENTAL MECHANICS

Volume 43, 2003

TITLE INDEX

A Critical Review of Microscale Mechanical Testing Methods Used in the Design of Microelectromechanical Systems—V. T. Srikar, S. M. Spearing, 238–247 (Sept.).

A New Method for the Biaxial Testing of Cellular Solids—D. Mohr, M. Doyoyo, 173–182 (June).

A Novel Instrument for Transient Photoelasticity—J. W. Hobbs, R. J. Greene and E. A. Patterson, 403–419 (Dec.).

A Polymeric Split Hopkinson Pressure Bar Instrumented With Velocity Gages—D. Casem, W. L. Fourney and P. Chang, 420–427 (Dec.).

A Review of MEMS-Based Microscale and Nanoscale Tensile and Bending Testing—M. A. Haque, M. T. A. Saif, 248–255 (Sept.).

An Experimental/Computational Approach to Identify Moduli and Residual Stress in MEMS Radio-Frequency Switches—H. D. Espinosa, Y. Zhu, M. Fischer and J. Hutchinson, 309–316 (Sept.).

An Open-Loop Control Scheme for Minimization of Residual Vibrations of A Flexible Robot—W. S. Jang, K.-S. Kim and S.-K. Lee, 387–395 (Dec.).

Determination of Dynamic Fracture-Initiation Toughness Using Three-Point Bending Tests in A Modified Hopkinson Pressure Bar—L. Rubio, J. Fernandez-Saez and C. Navarro, 379–386 (Dec.).

Determination of Residual Stresses by an Optical Correlative Hole-drilling Method—G. Focht, K. Schiffner, 97–104 (Mar.).

Development of a Portable Shear Test Fixture for Low Modulus Porous (Foam) Materials—A. K. Roy, J. D. Camping, 39–44 (Mar.).

Digital Speckle Correlation for Strain Measurement by Image Analysis—D. Amodio, G. B. Broggiato, F. Campana and G. M. Newaz, 396–402 (Dec.).

Dynamic Small Strain Measurements of a Metal Specimen with a Split Hopkinson Pressure Bar—W. W. Chen, B. Song, D. J. Frew and M. J. Forrestal, 20–23 (Mar.).

Dynamic Torsion Testing of Nanocrystalline Coatings Using High-Speed Photography and Digital Image Correlation—F. Barthelat, Z. Wu, B. C. Prorok and H. D. Espinosa, 331–340 (Sept.).

Editorial—N. R. Sottos, 372 (Dec.).

Elastic Moduli of the Piezoelectric Cochlear Outer Hair Cell Membrane—A. A. Spector, R. P. Jean, 355–360 (Sept.).

Elastic-Plastic Contact Mechanics of Indentations Accounting for Phase Transformations—B. A. Galanov, V. Domnich and Y. Gogotsi, 303–308 (Sept.).

Experimental Dynamic Analysis of Elastic-Plastic Shear Frames with Secondary Structures—C. Adam, R. Heuer and A. Pirrotta, 124–130 (June).

Fatigue Damage Evolution in Silicon Films for Micromechanical Applications—P. Shrotriya, S. Allameh, S. Brown, Z. Suo and W. O. Soboyejo, 289–302 (Sept.).

Field Measured Pre-stress Concrete Losses Versus Design Code Estimates—O. U. Onyemelukwe, P. E. Moussa Issa and C. J. Mills, 201–215, (June).

Fourier and Wavelet Analyses for Fatigue Assessment of Concrete Beams—H. Kim, H. Melhem, 131–140 (June).

Full-field Strain Measurement using a Luminescent Coating—J. P. Hubner, P. G. Ifju, K. S. Schanze, D. A. Jenkins, B. F. Carroll, Y. Wang, P. He, A. Brennan and W. El-Ratal, 61–68 (Mar.).

Hybrid Determination of Equivalent Characteristics of Perforated Plates—W.-C. Wang, K.-H. Lai, 163–172 (June).

Inspection of Interfaces Between Corroded Steel Bars and Concrete using the Combination of a Piezoelectric Zirconate-titanate Transducer and an Electromagnetic Acoustic Transducer—W.-B. Na, T. Kundu, 24–31 (Mar.).

Measurement of Residual Internal Stresses in Optical Fiber Preforms—L. Pagnotta, A.Poggialini, 69–76 (Mar.).

Measurement Techniques in the Testing of Thin-walled Structural Members—B. Young, K. J. R. Rasmussen, 32–38 (Mar.).

Mechanical Measurements of Adhesion in Microcantilevers: Transitions in Geometry and Cyclic Energy Changes—E. E. Jones, K. D. Murphy and M. R. Begley, 280–288 (Sept.).

Mechanical Properties of Ultrananocrystalline Diamond Thin Films Relevant to MEMS/NEMS Devices—H. D. Espinosa, B. C. Prorok, B. Peng, K. H. Kim, N. Moldovan, O. Auciello, J. A. Carlisle, D. M. Gruen and D. C. Mancini, 256–268 (Sept.).

Microelectromechanical Systems and Nanomaterials: Experimental and Computational Mechanics Aspects—H. D. Espinosa, 225–227 (Sept.).

Mixed-Mode Failure of Thin Films Using Laser-Generated Shear Waves—J. Wang, N. R. Sottos and R. L. Weaver, 323–330 (Sept.).

Murray Lecture: Tensile Testing at the Micrometer Scale: Opportunities in Experimental Mechanics—W. N. Sharpe, 228–237 (Sept.).

On the Use of Stereolithography for the Manufacture of Photoelastic Models—J. D. Curtis, S. D. Hanna, E. A. Patterson and M. Taroni, 148–162 (June).

Overview of Optical Techniques That Measure Displacements: Murray Lecture—C. A. Sciammarella, 1–19 (Mar.).

Performance Evaluation of Accelerometers Used for Penetration Experiments—M. J. Forrestal, T. C. Togami, W. E. Baker and D. J. Frew, 90–96 (Mar.).

Photoelastic Validation of A Theoretical Solution for An Edge Cracked Disk—M. Karpenko, Q. Wu, 410–419 (Dec.).

Piezoelectric Wafer Active Sensor Embedded Ultrasonics in Beams and Plates—V. Giurgiutiu, J. J. Bao and W. Zhao, 428–449 (Dec.).

Predictions of First-ply Failure Load of Laminated Composite Shafts—R. R. Chang, J. M. Chu, 183–193 (June).

Process Pathway Inference via Time Series Analysis—C. Wiggins, I. Nemenman, 361–370 (Sept.).

Processing and Characterization of Epoxy/Clay Nanocomposites—I. M. Daniel, H. Miyagawa, E. E. Gdoutos and J. J. Luo, 348–354 (Sept.).

Qualitative and Quantitative Evaluation of the Interface in Activated Shape Memory Alloy Composites—Y. Zheng, J. Schrooten, K. A. Tsoi and P. Šittner, 194–200, (June).

Real-time Analysis of Isochromatics and Isoclinics Using the Phase-shifting Method-S. Yoneyama, Y. Morimoto, T. Nomura, M. Fujigaki and R. Matsui, 83–89 (Mar.).

Reduction of KI and KII by the Shape-memory Effect in a TiNi Shape-memory Fiber-reinforced Epoxy Matrix Composite—A. Shimamoto, T. Azakami and T. Oguchi, 77–82 (Mar.).

Residual Stiffness Assessment of structurally Failed RC Structure by Dynamic Testing and FE Model Updating—P.-Q. Xia, J. M. W. Brownjohn, 372–378 (Dec.).

Residual Stress Distribution on Surface-treated Ti-6Al-4V by X-ray Diffraction—S. A. Martinez, S. Sathish, M. P. Blodgett and M. J. Shepard, 141–147 (June).

Strain Analysis for Moiré Interferometry Using the Two-dimensional Continuous Wavelet Transform—K. Kadooka, K. Kunoo, N. Uda, K. Ono and T. Nagayasu, 45–51 (Mar.).

Strain Measurements in the Nanometer Range in a Particulate Com-

Index to

EXPERIMENTAL MECHANICS

Volume 43, 2003

TITLE INDEX

A Critical Review of Microscale Mechanical Testing Methods Used in the Design of Microelectromechanical Systems—V. T. Srikar, S. M. Spearing, 238–247 (Sept.).

A New Method for the Biaxial Testing of Cellular Solids—D. Mohr, M. Doyoyo, 173–182 (June).

A Novel Instrument for Transient Photoelasticity—J. W. Hobbs, R. J. Greene and E. A. Patterson, 403–419 (Dec.).

A Polymeric Split Hopkinson Pressure Bar Instrumented With Velocity Gages—D. Casem, W. L. Fourney and P. Chang, 420–427 (Dec.).

A Review of MEMS-Based Microscale and Nanoscale Tensile and Bending Testing—M. A. Haque, M. T. A. Saif, 248–255 (Sept.).

An Experimental/Computational Approach to Identify Moduli and Residual Stress in MEMS Radio-Frequency Switches—H. D. Espinosa, Y. Zhu, M. Fischer and J. Hutchinson, 309–316 (Sept.).

An Open-Loop Control Scheme for Minimization of Residual Vibrations of A Flexible Robot—W. S. Jang, K.-S. Kim and S.-K. Lee, 387–395 (Dec.).

Determination of Dynamic Fracture-Initiation Toughness Using Three-Point Bending Tests in A Modified Hopkinson Pressure Bar—L. Rubio, J. Fernandez-Saez and C. Navarro, 379–386 (Dec.).

Determination of Residual Stresses by an Optical Correlative Hole-drilling Method—G. Focht, K. Schiffner, 97–104 (Mar.).

Development of a Portable Shear Test Fixture for Low Modulus Porous (Foam) Materials—A. K. Roy, J. D. Camping, 39–44 (Mar.).

Digital Speckle Correlation for Strain Measurement by Image Analysis—D. Amodio, G. B. Broggiato, F. Campana and G. M. Newaz, 396–402 (Dec.).

Dynamic Small Strain Measurements of a Metal Specimen with a Split Hopkinson Pressure Bar—W. W. Chen, B. Song, D. J. Frew and M. J. Forrestal, 20–23 (Mar.).

Dynamic Torsion Testing of Nanocrystalline Coatings Using High-Speed Photography and Digital Image Correlation—F. Barthelat, Z. Wu, B. C. Prorok and H. D. Espinosa, 331–340 (Sept.).

Editorial—N. R. Sottos, 372 (Dec.).

Elastic Moduli of the Piezoelectric Cochlear Outer Hair Cell Membrane—A. A. Spector, R. P. Jean, 355–360 (Sept.).

Elastic-Plastic Contact Mechanics of Indentations Accounting for Phase Transformations—B. A. Galanov, V. Domnich and Y. Gogotsi, 303–308 (Sept.).

Experimental Dynamic Analysis of Elastic-Plastic Shear Frames with Secondary Structures—C. Adam, R. Heuer and A. Pirrotta, 124–130 (June).

Fatigue Damage Evolution in Silicon Films for Micromechanical Applications—P. Shrotriya, S. Allameh, S. Brown, Z. Suo and W. O. Soboyejo, 289–302 (Sept.).

Field Measured Pre-stress Concrete Losses Versus Design Code Estimates—O. U. Onyemelukwe, P. E. Moussa Issa and C. J. Mills, 201–215, (June).

Fourier and Wavelet Analyses for Fatigue Assessment of Concrete Beams—H. Kim, H. Melhem, 131–140 (June).

Full-field Strain Measurement using a Luminescent Coating—J. P. Hubner, P. G. Ifju, K. S. Schanze, D. A. Jenkins, B. F. Carroll, Y. Wang, P. He, A. Brennan and W. El-Ratal, 61–68 (Mar.).

Hybrid Determination of Equivalent Characteristics of Perforated Plates—W.-C. Wang, K.-H. Lai, 163–172 (June).

Inspection of Interfaces Between Corroded Steel Bars and Concrete using the Combination of a Piezoelectric Zirconate-titanate Transducer and an Electromagnetic Acoustic Transducer—W.-B. Na, T. Kundu, 24–31 (Mar.).

Measurement of Residual Internal Stresses in Optical Fiber Preforms—L. Pagnotta, A.Poggialini, 69–76 (Mar.).

Measurement Techniques in the Testing of Thin-walled Structural Members—B. Young, K. J. R. Rasmussen, 32–38 (Mar.).

Mechanical Measurements of Adhesion in Microcantilevers: Transitions in Geometry and Cyclic Energy Changes—E. E. Jones, K. D. Murphy and M. R. Begley, 280–288 (Sept.).

Mechanical Properties of Ultrananocrystalline Diamond Thin Films Relevant to MEMS/NEMS Devices—H. D. Espinosa, B. C. Prorok, B. Peng, K. H. Kim, N. Moldovan, O. Auciello, J. A. Carlisle, D. M. Gruen and D. C. Mancini, 256–268 (Sept.).

Microelectromechanical Systems and Nanomaterials: Experimental and Computational Mechanics Aspects—H. D. Espinosa, 225–227 (Sept.).

Mixed-Mode Failure of Thin Films Using Laser-Generated Shear Waves—J. Wang, N. R. Sottos and R. L. Weaver, 323–330 (Sept.).

Murray Lecture: Tensile Testing at the Micrometer Scale: Opportunities in Experimental Mechanics—W. N. Sharpe, 228–237 (Sept.).

On the Use of Stereolithography for the Manufacture of Photoelastic Models—J. D. Curtis, S. D. Hanna, E. A. Patterson and M. Taroni, 148–162 (June).

Overview of Optical Techniques That Measure Displacements: Murray Lecture—C. A. Sciammarella, 1–19 (Mar.).

Performance Evaluation of Accelerometers Used for Penetration Experiments—M. J. Forrestal, T. C. Togami, W. E. Baker and D. J. Frew, 90–96 (Mar.).

Photoelastic Validation of A Theoretical Solution for An Edge Cracked Disk—M. Karpenko, Q. Wu, 410–419 (Dec.).

Piezoelectric Wafer Active Sensor Embedded Ultrasonics in Beams and Plates—V. Giurgiutiu, J. J. Bao and W. Zhao, 428–449 (Dec.).

Predictions of First-ply Failure Load of Laminated Composite Shafts—R. R. Chang, J. M. Chu, 183–193 (June).

Process Pathway Inference via Time Series Analysis—C. Wiggins, I. Nemenman, 361–370 (Sept.).

Processing and Characterization of Epoxy/Clay Nanocomposites—I. M. Daniel, H. Miyagawa, E. E. Gdoutos and J. J. Luo, 348–354 (Sept.).

Qualitative and Quantitative Evaluation of the Interface in Activated Shape Memory Alloy Composites—Y. Zheng, J. Schrooten, K. A. Tsoi and P. Šittner, 194–200, (June).

Real-time Analysis of Isochromatics and Isoclinics Using the Phase-shifting Method-S. Yoneyama, Y. Morimoto, T. Nomura, M. Fujigaki and R. Matsui, 83–89 (Mar.).

Reduction of KI and KII by the Shape-memory Effect in a TiNi Shape-memory Fiber-reinforced Epoxy Matrix Composite—A. Shimamoto, T. Azakami and T. Oguchi, 77–82 (Mar.).

Residual Stiffness Assessment of structurally Failed RC Structure by Dynamic Testing and FE Model Updating—P.-Q. Xia, J. M. W. Brownjohn, 372–378 (Dec.).

Residual Stress Distribution on Surface-treated Ti-6Al-4V by X-ray Diffraction—S. A. Martinez, S. Sathish, M. P. Blodgett and M. J. Shepard, 141–147 (June).

Strain Analysis for Moiré Interferometry Using the Two-dimensional Continuous Wavelet Transform—K. Kadooka, K. Kunoo, N. Uda, K. Ono and T. Nagayasu, 45–51 (Mar.).

Strain Measurements in the Nanometer Range in a Particulate Com-

posite Using Computer-Aided Moiré—C. A. Sciammarella, F. M. Sciammarella and T. Kim, 341–347 (Sept.).
Stress Wave Interference Effects during Fracture of Silicon Micromachined Specimens—A. M. Fitzgerald, T. W. Kenny and R. H. Dauskardt, 317–322 (Sept.).
Theoretical Analysis and Digital Photoelastic Measurement of Circular Disks Subjected to Partially Distributed Compressions—K.-M. Hung, C.-C. Ma, 216–224 (June).
Theoretical and Experimental Investigation of Ultrasonic Waves Radiated From A Wet Surface Using A Line-Focused Laser Beam—S.-C. Wooh, Q. Zhou and J. Wang, 450–459 (Dec.).
Thin Film Cracking Modulated by Underlayer Creep—J. Liang, R. Huang, J. H. Prévost and Z. Suo, 269–279 (Sept.).
Three-dimensional Size Effects in Composite Pin Joints—D. Liu, L. Hou, 115–123 (June).
Three-dimensional Stress-relief Displacements from Blind-hole Drilling: A Parametric Description—I. Rumzan, D. R. Schmitt, 52–60 (Mar.).
X-ray Residual Stress Measurement on Mechanical Components with High Curvature—T. Berruti, M. M. Gola, 105–114 (Mar.).

AUTHOR INDEX

Adam, C.—Experimental Dynamic Analysis of Elastic-Plastic Shear Frames with Secondary Structures, 124–130 (June).
Allameh, S.—Fatigue Damage Evolution in Silicon Films for Micromechanical Applications, 289–302 (Sept.).
Amodio, D.—Digital Speckle Correlation for Strain Measurement by Image Analysis, 396–402 (Dec.).
Auciello, O.—Mechanical Properties of Ultrananocrystalline Diamond Thin Films Relevant to MEMS/NEMS Devices, 256–268 (Sept.).
Azakami, T.—Reduction of KI and KII by the Shape-memory Effect in a TiNi Shape-memory Fiber-reinforced Epoxy Matrix Composite, 77–82 (Mar.).
Baker, W. E.—Performance Evaluation of Accelerometers Used for Penetration Experiments, 90–96 (Mar.).
Bao, J. J.—Piezoelectric Wafer Active Sensor Embedded Ultrasonics in Beams and Plates, 428–449 (Dec.).
Barthelat, F.—Dynamic Torsion Testing of Nanocrystalline Coatings Using High-Speed Photography and Digital Image Correlation, 331–340 (Sept.).
Begley, M. R.—Mechanical Measurements of Adhesion in Microcantilevers: Transitions in Geometry and Cyclic Energy Changes, 280–288 (Sept.).
Berruti, T.—X-ray Residual Stress Measurement on Mechanical Components with High Curvature, 105–114, (Mar.)
Blodgett, M. P.—Residual Stress Distribution on Surface-treated Ti-6Al-4V by X-ray Diffraction, 141–147 (June).
Brennan, A.—Full-field Strain Measurement using a Luminescent Coating, 61–68 (Mar.).
Broggiato, G. B.—Digital Speckle Correlation for Strain Measurement by Image Analysis, 396–402 (Dec.).
Brown, S.—Fatigue Damage Evolution in Silicon Films for Micromechanical Applications, 289–302 (Sept.).
Brownjohn, J. M. W.—Residual stiffness assessment of structurally failed RC structure by dynamic testing and FE model updating, 372–378 (Dec.).
Campana, F.—Digital Speckle Correlation for Strain Measurement by Image Analysis, 396–402 (Dec.).
Camping, J. D.—Development of a Portable Shear Test Fixture for Low Modulus Porous (Foam) Materials, 39–44 (Mar.).
Carlisle, J. A.—Mechanical Properties of Ultrananocrystalline Diamond Thin Films Relevant to MEMS/NEMS Devices, 256–268 (Sept.).
Carroll, B. F.—Full-field Strain Measurement using a Luminescent Coating, 61–68 (Mar.).
Casem, D.—A Polymeric Split Hopkinson Pressure Bar Instrumented With Velocity Gages, 420–427 (Dec.).
Chang, P.—A Polymeric Split Hopkinson Pressure Bar Instrumented With Velocity Gages, 420–427 (Dec.).
Chang, R. R.—Predictions of First-ply Failure Load of Laminated Composite Shafts, 183–193 (June).
Chen, W. W.—Dynamic Small Strain Measurements of a Metal Specimen with a Split Hopkinson Pressure Bar, 20–23 (Mar.).
Chu, J. M.—Predictions of First-ply Failure Load of Laminated Composite Shafts, 183–193 (June).
Curtis, J. D.—On the Use of Stereolithography for the Manufacture of Photoelastic Models, 148–162 (June).
Daniel, I. M.—Processing and Characterization of Epoxy/Clay Nanocomposites, 348–354 (Sept.).
Dauskardt, R. H.—Stress Wave Interference Effects during Fracture of Silicon Micromachined Specimens, 317–322 (Sept.).
Domnich, V.—Elastic-Plastic Contact Mechanics of Indentations Accounting for Phase Transformations, 303–308 (Sept.).
Doyoyo, M.—A New Method for the Biaxial Testing of Cellular Solids, 173–182 (June).
El-Ratal, W.—Full-field Strain Measurement using a Luminescent Coating, 61–68 (Mar.).
Espinosa, H. D.—An Experimental/Computational Approach to Identify Moduli and Residual Stress in MEMS Radio-Frequency Switches, 309–316 (Sept.).
Espinosa, H. D.—Dynamic Torsion Testing of Nanocrystalline Coatings Using High-Speed Photography and Digital Image Correlation, 331–340 (Sept.).
Espinosa, H. D.—Mechanical Properties of Ultrananocrystalline Diamond Thin Films Relevant to MEMS/NEMS Devices, 256–268 (Sept.).
Espinosa, H. D.—Microelectromechanical Systems and Nanomaterials: Experimental and Computational Mechanics Aspects, 225–227 (Sept.).
Fernandez-Saez, J.—Determination of Dynamic Fracture-Initiation Toughness Using Three-Point Bending Tests in A Modified Hopkinson Pressure Bar, 379–386 (Dec.).
Fischer, M.—An Experimental/Computational Approach to Identify Moduli and Residual Stress in MEMS Radio-Frequency Switches, 309–316 (Sept.).
Fitzgerald, A. M.—Stress Wave Interference Effects during Fracture of Silicon Micromachined Specimens, 317–322 (Sept.).
Focht, G.—Determination of Residual Stresses by an Optical Correlative Hole-drilling Method, 97–104 (Mar.).
Forrestal, M. J.—Dynamic Small Strain Measurements of a Metal Specimen with a Split Hopkinson Pressure Bar, 20–23 (Mar.).
Forrestal, M. J.—Performance Evaluation of Accelerometers Used for Penetration Experiments, 90–96 (Mar.).
Fourney, W. L.—A Polymeric Split Hopkinson Pressure Bar Instrumented With Velocity Gages, 420–427 (Dec.).
Frew, D. J.—Dynamic Small Strain Measurements of a Metal Specimen with a Split Hopkinson Pressure Bar, 20–23 (Mar.).
Frew, D. J.—Performance Evaluation of Accelerometers Used for Penetration Experiments, 90–96 (Mar.).
Fujigaki, M.—Real-time Analysis of Isochromatics and Isoclinics Using the Phase-shifting Method, 83–89 (Mar.).
Galanov, B. A.—Elastic-Plastic Contact Mechanics of Indentations Accounting for Phase Transformations, 303–308 (Sept.).
Gdoutos, E. E.—Processing and Characterization of Epoxy/Clay Nanocomposites, 348–354 (Sept.).
Giurgiutiu, V.—Piezoelectric Wafer Active Sensor Embedded Ultrasonics in Beams and Plates, 428–449 (Dec.).
Gogotsi, Y.—Elastic-Plastic Contact Mechanics of Indentations Accounting for Phase Transformations, 303–308 (Sept.).
Gola, M. M.—X-ray Residual Stress Measurement on Mechanical Components with High Curvature, 105–114 (Mar.)
Greene, R. J.—A Novel Instrument for Transient Photoelasticity, 403–409 (Dec.).
Gruen, D. M.—Mechanical Properties of Ultrananocrystalline Diamond Thin Films Relevant to MEMS/NEMS Devices, 256–268 (Sept.).
Hanna, S. D.—On the Use of Stereolithography for the Manufacture of Photoelastic Models, 148–162 (June).
Haque, M. A.—A Review of MEMS-Based Microscale and Nanoscale Tensile and Bending Testing, 248–255 (Sept.).
He, P.—Full-field Strain Measurement using a Luminescent Coating, 61–68 (Mar.).
Heuer, R.—Experimental Dynamic Analysis of Elastic-Plastic Shear Frames with Secondary Structures, 124–130 (June).

Hobbs, J. W.—A Novel Instrument for Transient Photoelasticity, 403–409 (Dec.).
Hou, L.—Three-dimensional Size Effects in Composite Pin Joints, 115–123 (June).
Huang, R.—Thin Film Cracking Modulated by Underlayer Creep, 269–279 (Sept.).
Hubner, J. P.—Full-field Strain Measurement using a Luminescent Coating, 61–68 (Mar.).
Hung, K.-M.—Theoretical Analysis and Digital Photoelastic Measurement of Circular Disks Subjected to Partially Distributed Compressions, 216–224 (June).
Hutchinson, J.—An Experimental/Computational Approach to Identify Moduli and Residual Stress in MEMS Radio-Frequency Switches, 309–316 (Sept.).
Ifju, P. G.—Full-field Strain Measurement using a Luminescent Coating, 61–68 (Mar.).
Jang, W. S.—An Open-Loop Control Scheme for Minimization of Residual Vibrations of A Flexible Robot, 387–395 (Dec.).
Jean, R. P.—Elastic Moduli of the Piezoelectric Cochlear Outer Hair Cell Membrane, 355–360 (Sept.).
Jenkins, D. A.—Full-field Strain Measurement using a Luminescent Coating, 61–68 (Mar.).
Jones, E. E.—Mechanical Measurements of Adhesion in Microcantilevers: Transitions in Geometry and Cyclic Energy Changes, 280–288 (Sept.).
Kadooka, K.—Strain Analysis for Moiré Interferometry Using the Two-dimensional Continuous Wavelet Transform, 45–51 (Mar.).
Karpenko, M.—Photoelastic Validation of A Theoretical Solution for An Edge Cracked Disk, 410–419 (Dec.).
Kenny, T. W.—Stress Wave Interference Effects during Fracture of Silicon Micromachined Specimens, 317–322 (Sept.).
Kim, H.—Fourier and Wavelet Analyses for Fatigue Assessment of Concrete Beams, 131–140 (June).
Kim, K. H.—Mechanical Properties of Ultrananocrystalline Diamond Thin Films Relevant to MEMS/NEMS Devices, 256–268 (Sept.).
Kim, K.-S.—An Open-Loop Control Scheme for Minimization of Residual Vibrations of A Flexible Robot, 387–395 (Dec.).
Kim, T.—Strain Measurements in the Nanometer Range in a Particulate Composite Using Computer-Aided Moiré, 341–347 (Sept.).
Kundu, T.—Inspection of Interfaces Between Corroded Steel Bars and Concrete using the Combination of a Piezoelectric Zirconate-titanate Transducer and an Electromagnetic Acoustic Transducer, 24–31 (Mar.).
Kunoo, K.—Strain Analysis for Moiré Interferometry Using the Two-dimensional Continuous Wavelet Transform, 45–51 (Mar.).
Lai, K.-H.—Hybrid Determination of Equivalent Characteristics of Perforated Plates, 163–172 (June).
Lee, S.-K.—An Open-Loop Control Scheme for Minimization of Residual Vibrations of A Flexible Robot, 387–395 (Dec.).
Liang, J.—Thin Film Cracking Modulated by Underlayer Creep, 269–279 (Sept.).
Liu, D.—Three-dimensional Size Effects in Composite Pin Joints, 115–123 (June).
Luo, J. J.—Processing and Characterization of Epoxy/Clay Nanocomposites, 348–354 (Sept.).
Ma, C.-C.—Theoretical Analysis and Digital Photoelastic Measurement of Circular Disks Subjected to Partially Distributed Compressions, 216–224 (June).
Mancini, D. C.—Mechanical Properties of Ultrananocrystalline Diamond Thin Films Relevant to MEMS/NEMS Devices, 256–268 (Sept.).
Martinez, S. A.—Residual Stress Distribution on Surface-treated Ti-6Al-4V by X-ray Diffraction, 141–147 (June).
Matsui, R.—Real-time Analysis of Isochromatics and Isoclinics Using the Phase-shifting Method, 83–89 (Mar.).
Melhem, H.—Fourier and Wavelet Analyses for Fatigue Assessment of Concrete Beams, 131–140 (June).
Mills, C. J.—Field Measured Pre-stress Concrete Losses Versus Design Code Estimates, 201–215 (June).
Miyagawa, H.—Processing and Characterization of Epoxy/Clay Nanocomposites, 348–354 (Sept.).
Mohr, D.—A New Method for the Biaxial Testing of Cellular Solids, 173–182 (June).
Moldovan, N.—Mechanical Properties of Ultrananocrystalline Diamond Thin Films Relevant to MEMS/NEMS Devices, 256–268 (Sept.).
Moussa Issa, P. E.—Field Measured Pre-stress Concrete Losses Versus Design Code Estimates, 201–215 (June).
Murphy, K. D.—Mechanical Measurements of Adhesion in Microcantilevers: Transitions in Geometry and Cyclic Energy Changes, 280–288 (Sept.).
Na, W.-B.—Inspection of Interfaces Between Corroded Steel Bars and Concrete using the Combination of a Piezoelectric Zirconate-titanate Transducer and an Electromagnetic Acoustic Transducer, 24–31 (Mar.).
Nagayasu, T.—Strain Analysis for Moiré Interferometry Using the Two-dimensional Continuous Wavelet Transform, 45–51 (Mar.).
Navarro, C.—Determination of Dynamic Fracture-Initiation Toughness Using Three-Point Bending Tests in A Modified Hopkinson Pressure Bar, 379–386 (Dec.).
Nemenman, I.—Process Pathway Inference via Time Series Analysis, 361–370 (Sept.).
Newaz, G. M.—Digital Speckle Correlation for Strain Measurement by Image Analysis, 396–402 (Dec.).
Oguchi, T.—Reduction of KI and KII by the Shape-memory Effect in a TiNi Shape-memory Fiber-reinforced Epoxy Matrix Composite, 77–82 (Mar.).
Ono, K.—Strain Analysis for Moiré Interferometry Using the Two-dimensional Continuous Wavelet Transform, 45–51 (Mar.).
Onyemelukwe, O. U.—Field Measured Pre-stress Concrete Losses Versus Design Code Estimates, 201–215 (June).
Pagnotta, L.—Measurement of Residual Internal Stresses in Optical Fiber Preforms, 69–76 (Mar.).
Patterson, E. A.—A Novel Instrument for Transient Photoelasticity, 403–409 (Dec.).
Patterson, E. A.—On the Use of Stereolithography for the Manufacture of Photoelastic Models, 148–162 (June).
Peng, B.—Mechanical Properties of Ultrananocrystalline Diamond Thin Films Relevant to MEMS/NEMS Devices, 256–268 (Sept.).
Pirrotta, A.—Experimental Dynamic Analysis of Elastic-Plastic Shear Frames with Secondary Structures, 124–130 (June).
Poggialini, A.—Measurement of Residual Internal Stresses in Optical Fiber Preforms, 69–76 (Mar.).
Prévost, J. H.—Thin Film Cracking Modulated by Underlayer Creep, 269–279 (Sept.).
Prorok, B. C.—Dynamic Torsion Testing of Nanocrystalline Coatings Using High-Speed Photography and Digital Image Correlation, 331–340 (Sept.).
Prorok, B. C.—Mechanical Properties of Ultrananocrystalline Diamond Thin Films Relevant to MEMS/NEMS Devices, 256–268 (Sept.).
Rasmussen, K. J. R.—Measurement Techniques in the Testing of Thin-walled Structural Members, 32–38 (Mar.).
Roy, A. K.—Development of a Portable Shear Test Fixture for Low Modulus Porous (Foam) Materials, 39–44 (Mar.).
Rubio, L.—Determination of Dynamic Fracture-Initiation Toughness Using Three-Point Bending Tests in A Modified Hopkinson Pressure Bar, 379–386 (Dec.).
Rumzan, I.—Three-dimensional Stress-relief Displacements from Blind-hole Drilling: a Parametric Description, 52–60 (Mar.).
Saif, M. T. A.—A Review of MEMS-Based Microscale and Nanoscale Tensile and Bending Testing, 248–255 (Sept.).
Sathish, S.—Residual Stress Distribution on Surface-treated Ti-6Al-4V by X-ray Diffraction, 141–147 (June).
Schanze, K. S.—Full-field Strain Measurement using a Luminescent Coating, 61–68 (Mar.).
Schiffner, K.—Determination of Residual Stresses by an Optical Correlative Hole-drilling Method, 97–104 (Mar.).
Schmitt, D. R.—Three-dimensional Stress-relief Displacements from Blind-hole Drilling: a Parametric Description, 52–60 (Mar.).
Schrooten, J.—Qualitative and Quantitative Evaluation of the Interface in Activated Shape Memory Alloy Composites, 194–200 (June).
Sciammarella, C. A.—Overview of Optical Techniques That Measure Displacements: Murray Lecture, 1–19 (Mar.).
Sciammarella, C. A.—Strain Measurements in the Nanometer Range in a Particulate Composite Using Computer-Aided Moiré, 341–347 (Sept.).

Sciammarella, F. M.—Strain Measurements in the Nanometer Range in a Particulate Composite Using Computer-Aided Moiré, 341–347 (Sept.).
Sharpe, W. N.—Murray Lecture: Tensile Testing at the Micrometer Scale: Opportunities in Experimental Mechanics, 228–237 (Sept.).
Shepard, M. J.—Residual Stress Distribution on Surface-treated Ti-6Al-4V by X-ray Diffraction, 141–147 (June).
Shimamoto, A.—Reduction of KI and KII by the Shape-memory Effect in a TiNi Shape-memory Fiber-reinforced Epoxy Matrix Composite, 77–82 (Mar.).
Shrotriya, P.—Fatigue Damage Evolution in Silicon Films for Micromechanical Applications, 289–302 (Sept.).
Šittner, P.—Qualitative and Quantitative Evaluation of the Interface in Activated Shape Memory Alloy Composites, 194–200 (June).
Soboyejo, W. O.—Fatigue Damage Evolution in Silicon Films for Micromechanical Applications, 289–302 (Sept.).
Song, B.—Dynamic Small Strain Measurements of a Metal Specimen with a Split Hopkinson Pressure Bar, 20–23 (Mar.).
Sottos, N. R.—Editorial, 371 (Dec.).
Sottos, N. R.—Mixed-Mode Failure of Thin Films Using Laser-Generated Shear Waves, 323–330 (Sept.).
Spearing, S. M.—A Critical Review of Microscale Mechanical Testing Methods Used in the Design of Microelectromechanical Systems, 238–247 (Sept.).
Spector, A. A.—Elastic Moduli of the Piezoelectric Cochlear Outer Hair Cell Membrane, 355–360 (Sept.).
Srikar, V. T.—A Critical Review of Microscale Mechanical Testing Methods Used in the Design of Microelectromechanical Systems, 238–247 (Sept.).
Suo, Z.—Fatigue Damage Evolution in Silicon Films for Micromechanical Applications, 289–302 (Sept.).
Suo, Z.—Thin Film Cracking Modulated by Underlayer Creep, 269–279 (Sept.).
T. Nomura—Real-time Analysis of Isochromatics and Isoclinics Using the Phase-shifting Method, 83–89 (Mar.).
Taroni, M.—On the Use of Stereolithography for the Manufacture of Photoelastic Models, 148–162 (June).
Togami, T. C.—Performance Evaluation of Accelerometers Used for Penetration Experiments, 90–96 (Mar.).
Tsoi, K. A.—Qualitative and Quantitative Evaluation of the Interface in Activated Shape Memory Alloy Composites, 194–200 (June).
Uda, N.—Strain Analysis for Moiré Interferometry Using the Two-dimensional Continuous Wavelet Transform, 45–51 (Mar.).
Wang, J.—Mixed-Mode Failure of Thin Films Using Laser-Generated Shear Waves, 323–330 (Sept.).
Wang, J.—Theoretical and Experimental Investigation of Ultrasonic Waves Radiated From A Wet Surface Using A Line-Focused Laser Beam, 450–459 (Dec.).
Wang, W.-C.—Hybrid Determination of Equivalent Characteristics of Perforated Plates, 163–172 (June).
Wang, Y.—Full-field Strain Measurement using a Luminescent Coating, 61–68 (Mar.).
Weaver, R. L.—Mixed-Mode Failure of Thin Films Using Laser-Generated Shear Waves, 323–330 (Sept.).
Wiggins, C.—Process Pathway Inference via Time Series Analysis, 361–370 (Sept.).
Wooh, S.-C.—Theoretical and Experimental Investigation of Ultrasonic Waves Radiated From A Wet Surface Using A Line-Focused Laser Beam, 450–459 (Dec.).
Wu, Q.—Photoelastic Validation of A Theoretical Solution for An Edge Cracked Disk, 410–419 (Dec.).
Wu, Z.—Dynamic Torsion Testing of Nanocrystalline Coatings Using High-Speed Photography and Digital Image Correlation, 331–340 (Sept.).
Xia, P.-Q.—Residual stiffness assessment of structurally failed RC structure by dynamic testing and FE model updating, 372–378 (Dec.).
Y. Morimoto—Real-time Analysis of Isochromatics and Isoclinics Using the Phase-shifting Method, 83–89 (Mar.).
Yoneyama, S.—Real-time Analysis of Isochromatics and Isoclinics Using the Phase-shifting Method, 83–89, (Mar.).
Young, B.—Measurement Techniques in the Testing of Thin-walled Structural Members, 32–38 (Mar.).
Zhao, W.—Piezoelectric Wafer Active Sensor Embedded Ultrasonics in Beams and Plates, 428–449 (Dec.).
Zheng, Y.—Qualitative and Quantitative Evaluation of the Interface in Activated Shape Memory Alloy Composites, 194–200 (June).
Zhou, Q.—Theoretical and Experimental Investigation of Ultrasonic Waves Radiated From A Wet Surface Using A Line-Focused Laser Beam, 450–459 (Dec.).
Zhu, Y.—An Experimental/Computational Approach to Identify Moduli and Residual Stress in MEMS Radio-Frequency Switches, 309–316 (Sept.).